

Certificate of Conformity

This is to Certify **COLORSTEEL® DRIDEX®** and **COLORSTEEL® DRIDEX+®**

Product Description

COLORSTEEL® DRIDEX® and COLORSTEEL® DRIDEX+® are ZINCALUME® coated steel substrates to which a COLORSTEEL® prepainted finish system is applied and an absorbent CondenStop fleece applied to the backer coating.

Complies with the Building Code of New Zealand:

When used in accordance with the conditions and limitations of this certificate, COLORSTEEL® DRIDEX® and COLORSTEEL® DRIDEX+® will comply with the following New Zealand Building Code Clauses;

B2 Durability – B2.3.1 (b)

C3 Fire Affecting Areas Beyond The Fire Source – C3.4 (a)

E2 External Moisture – E2.3.1 (contributes to) E2.3.2, E2.3.5, E2.3.7

E3 Internal Moisture – E3.3.1

F2 Hazardous Building Material – F2.3.1

G12 Water Supplies – G12.3.1

Subject to the following conditions and limitations:

1. This Certificate applies to COLORSTEEL® DRIDEX® and COLORSTEEL® DRIDEX+® supplied for roof cladding only.
2. The profiles and minimum roof pitch for roof cladding shall be as specified in Acceptable Solution E2/AS1 paras 8.4.4 and 8.4.5.
3. The roof space must be ventilated, with the area of roof space ventilation openings equivalent to at least 1/300 of the ceiling area.
4. This certificate excludes the use of COLORSTEEL® DRIDEX® and COLORSTEEL® DRIDEX+® for skillion roofs.
5. Roofing underlay must not be used.
6. The top ends of roof cladding must have stopends as described in Acceptable Solution E2/AS1 para 8.4.13.
7. Must be installed in accordance with the COLORSTEEL® DRIDEX® Installation Guide V2.
8. New Zealand Steel Limited will notify AsureQuality in accordance with Regulation 15 of the Building (Product Certification) Regulations 2008.


John McKay, Chief Executive Officer, AsureQuality Limited

Date of Issue

4th September 2017

Certificate Number

AQ-040917-CMNZ
(Rev 1 – September 2017)



CODEMARK™

Product Use and Scope

This certificate covers COLORSTEEL® DRIDEX® and COLORSTEEL® DRIDEX+® used as a roof cladding system in accordance with the scope and provisions of Acceptable Solution E2/AS1 for profiled metal roof cladding with the exceptions that roofing underlay is eliminated from the roof construction and the roof space must be ventilated. COLORSTEEL® DRIDEX® may be used in mild and moderate environments; COLORSTEEL® DRIDEX+® may be used in mild, moderate and severe coastal environments (as specified in the *COLORSTEEL® DRIDEX® Product Brochure* and *New Zealand Steel Environmental Categories Brochure*, *Warranty* and *Product Maintenance Recommendations Brochure*).

Certificate Holder

New Zealand Steel Limited
131 Mission Bush Road
Glenbrook
Auckland
Ph: 09 375 8999
Email: info@colorsteel.co.nz
Web: www.nzsteel.co.nz



JAS-ANZ



www.jas-anz.org/register

CodeMark Certification Body

AsureQuality, 11 Hull Road
Mt Maunganui
New Zealand
Tel. 0508 00 11 22
www.asurequality.com

"This certificate is issued by an independent certification body accredited by the product certification accreditation body appointed by the Chief Executive of the Ministry of Business, Innovation and Employment (MBIE) under the Building Act 2004. The MBIE does not in any way warrant, guarantee, or represent that the building method or product the subject of this certificate conforms with the New Zealand Building Code, nor accept any liability arising out of the use of the building method or product. The MBIE disclaims, to the extent permitted by law, all liability (including negligence) for claims of losses, expenses, damages, and costs arising as a result of the use of the building method(s) or product(s) referred to in this certificate. This certificate may only be reproduced in its entirety."